

AEOS Locker Infopoint 7-inch touchscreen

AEOS Locker Management is an efficient addition to your access control system. And this stylish, 7-inch touchscreen display gives people all the information and functionality they need to use your lockers.



Makes lockers easy to operate

After presenting an identifier to the display, users can get information about the locker they've claimed or other lockers available to claim. The Infopoint needs to be connected with a reader. This reader isn't included.

If someone has claimed multiple lockers, for example, they're displayed on the touchscreen, and they can select which one to open. If a locker is assigned to a group rather than an individual, it will have an extra icon on the display. The touchscreen will also choose the correct layout for the user's role. If they have multiple roles, they can use the display to select which role to apply.

Puts users in control

Via an on-screen globe, users can also select which language to use on the touchscreen. And, by selecting the "I" key, they can get a concise explanation of how the locker system works.

Simple in design, this touchscreen is very intuitive with selection keys designed for easy operation for everyone. Powered by a Chromium web browser, the Infopoint directly connects to the controller and an AP7803 where the locker AEBcs are installed. For daily operations, the AEOS server isn't needed. Which assures you of an autonomous operation.

Technical specifications

| | |
|--------------------|--|
| Measurements | 131 x 97 x 31 mm (LxWxH) |
| Cut-out dimensions | 185 x 125 mm (WxH) |
| Display size | 7 inch |
| Weight | ~0,5 kg |
| Type | ESA EW107BD4SP |
| Display technology | TFT |
| Display colours | 16M |
| Display backlight | LED |
| Display brightness | 500 (cd/m2) |
| Display resolution | 1024 x 600 (pixel) |
| Backlight life | 50,000 hours |
| Touch technology | Capacitive |
| Processor | ARM Cortex A9 quad-core |
| RAM | 2GB DDR3L |
| Flash | 8 GB |
| Browser | Chromium |
| Ethernet port | 1 x 1GB + 1 x 10 / 100 Mb |
| USB | 2 x ver. 2.0 |
| Serial port | 1 x RS232/485 |
| Expansion slot | 1 x MINI PCI express |
| Cardbus slot | 1 x SDHC |
| Power supply | 12 – 32 (Vdc) |
| Consumption | 7w |
| Environment | Temperature: In operation: 0 °C - 50 °C. Storage: -20 - 65 °C. Relative humidity: >90% (non-condensing) |
| Protection degree | (front) IP66 |
| Certifications | CE / EN60068-2-6 / EN60068-2-27 / Humidity EN60068-2-30 |

Article number

| | |
|-----------------------|---------|
| AEOS Locker Infopoint | 9988408 |
|-----------------------|---------|

Subject to change without prior notification